

## Compressed Sheet Packing Aramid Fibers/EPDM Binder

### STYLE 1190

#### Construction/Description

##### Compressed Aramid Fiber Style 1190

Style 1190 is a compressed aramid fiber sheet gasket material produced by a combination of aramid and other synthetic fibers bonded with EPDM rubber. It is manufactured through the hot calendar process under rigorous quality control standards that are registered under ISO-9002 certification.

#### Application/Service

Style 1190 is a premium service sheet that provides an effective seal against mild acids and caustics. The EPDM Binder adds exceptional resistance to both weather aging and ozone. Style 1190 is suitable for service handling the following general media categories:

- » Mild Inorganic Acids
- » Mild Organic Acids
- » Concentrated Alkalies
- » Strong Inorganic Acids
- » Strong Organic Acids
- » Diluted Alkalies
- » Water
- » Air

*Style 1190 is not suitable for most seam applications*

#### Product Data

Temperature Limits		Pressure Limits	Color
Minimum	Limited Maximum		
-40°F 40°C	700°F 370°C	Vacuum to 1200 PSI (83 Bar)	Light Gray

#### *Service is Our Business*

For "Typical Physical Properties", P×T limits and Sealability Curve, please contact the Sales Department. Technical properties are typical and are presented in good faith, but no warranty is expressed or implied.

All technical advise and recommendation are rendered by Seller free of charge. While based on data believed to be reliable, seller assumes no responsibility.