



Gasket Dimensions for XR-RJ (RTJ)

1500#			
NPS Nominal Pipe Size	1500#		
	Gasket I.D.	Gasket O.D.	Guide Ring O.D.
1/2"	9-1/16"	1-1/16"	2-1/2"
3/4"	13/16"	1-3/8"	2-3/4"
1"	1-1/16"	1-5/8"	3-1/8"
1 1/4"	1-5/16"	2"	3-1/2"
1 1/2"	1-9/16"	2-3/8"	3-7/8"
2"	2-1/4"	3-1/4"	5-5/8"
2 1/2"	2-9/16"	3-5/8"	6-1/2"
3"	3-3/16"	4-11/16"	6-7/8"
4"	4-1/16"	5-11/16"	8-1/4"
5"	5-1/16"	6-15/16"	10"
6"	6"	7-9/16"	11-1/8"
8"	7-7/8"	9-3/4"	13-7/8"
10"	9-13/16"	11-7/8"	17-1/8"
12"	11-15/16"	13-13/16"	20-1/2"
14"	13-7/16"	15-3/16"	22-3/4"
16"	15"	17"	25-1/4"
18"	17-1/4"	19-1/2"	27-3/4"
20"	19-13/16"	21-7/16"	29-3/4"
24"	23"	25-1/2"	35-1/2"

Style XR-RJ is a replacement gasket for solid metal oval or octagonal API Ring Joint gasket.

These gaskets may be used as a replacement when spiral wound gaskets are preferred or when the gasket groove is badly worn, thereby saving the cost of flange replacement.

NOTE: O.D. Dimensions of gaskets are nominal. Actual dimensions are approximately 1/32" less to incur proper assembly in rings.