



Gasket Dimensions for XR-RJ (RTJ)

600#			
NPS Nominal Pipe Size	600#		
	Gasket I.D.	Gasket O.D.	Guide Ring O.D.
1/2"	9-1/16"	1-1/16"	2-1/8"
3/4"	13/16"	1-5/16"	2-5/8"
1"	1-1/16"	1-5/8"	2-7/8"
1 1/4"	1-5/16"	2"	3-1/4"
1 1/2"	1-9/16"	2-3/8"	3-3/4"
2"	2-1/8"	2-3/4"	4-3/8"
2 1/2"	2-3/4"	3-5/16"	5-1/8"
3"	3-5/16"	3-15/16"	5-7/8"
4"	4-5/16"	5-3/16"	7-5/8"
5"	5-5/16"	6-7/16"	9-1/2"
6"	6-7/16"	7-5/8"	10-1/2"
8"	8-1/4"	9-15/16"	12-5/8"
10"	10-5/16"	12"	15-3/4"
12"	12-7/8"	14-1/4"	18"
14"	14-1/4"	15-3/4"	19-3/8"
16"	16-1/4"	17-3/4"	22-1/4"
18"	18-1/4"	20-1/4"	23-3/8"
20"	20-1/4"	22-3/16"	26-7/8"
24"	24-1/4"	26-5/16"	31-1/8"

Style XR-RJ is a replacement gasket for solid metal oval or octagonal API Ring Joint gasket.

These gaskets may be used as a replacement when spiral wound gaskets are preferred or when the gasket groove is badly worn, thereby saving the cost of flange replacement.

NOTE: O.D. Dimensions of gaskets are nominal. Actual dimensions are approximately 1/32" less to incur proper assembly in rings.